

Network Polymers NPP 50-0753

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

Material Notes:

Description: High Density Polyethylene (HDPE) Information provided by Network Polymers Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Network-Polymers-NPP-50-0753.php

Physical Properties	Metric	English	Comments
Density	0.953 g/cc	0.0344 lb/in ³	ASTM D1505
Melt Flow	7.0 g/10 min @Load 2.16 kg, Temperature 190 °C	7.0 g/10 min @Load 4.76 lb, Temperature 374 °F	Procedure A Condition E; ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	30.0 MPa	4350 psi	chs 2 in/min; ASTM D638
Elongation at Break	950 %	950 %	ASTM D638
Flexural Modulus	1.24 GPa	180 ksi	Test Method I, Procedure B (chs speed 0.05 in/min); ASTM D790

Thermal Properties	Metric	English	Comments
Brittleness Temperature	<= -76.1 °C	<= -105 °F	ASTM D746

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China