

Network Polymers NPP 50-5052

Category : Polymer , Thermoplastic , Polyethylene (PE) , HDPE , High Density Polyethylene (HDPE), Injection Molded

Material Notes:

Description: High Density Polyethylene (HDPE) Information provided by Network Polymers Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Network-Polymers-NPP-50-5052.php

Physical Properties	Metric	English	Comments
Density	0.952 g/cc	0.0344 lb/in ³	ASTM D1505
Melt Flow	46 - 50 g/10 min @Load 2.16 kg, Temperature 230 °C	46 - 50 g/10 min @Load 4.76 lb, Temperature 446 °F	Procedure A Condition L; ASTM D1238

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	24.8 MPa	3600 psi	chs 2 in/min; ASTM D638
Elongation at Break	4.0 %	4.0 %	chs 2 in/min; ASTM D638
Flexural Modulus	1.07 GPa	155 ksi	Test Method I, Procedure B (chs speed 0.05 in/min); ASTM D790

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China