

Neutrex Purgex™ 457 Purging Compound

Category : Polymer , Thermoplastic , Purging Compound

Material Notes:

Blend, polyethylene, 3% glass, and an FDA-approved active component. Non-toxic, non-abrasive, and safe. Ready to use and easy to remove. PURGEX 457 Plus is used for color and/or material changes and the removal of residual contamination in thermoplastic injection molding, extrusion, or blow molding equipment. PURGEX 457 Plus will efficiently purge the barrel, screw, and nozzle, as well as hot runner systems, removing all types of colorants and commodity resins, including polypropylene, polyethylene, and their copolymers, particularly if they contain glass or fillers. PURGEX 457 Plus assures rapid turnaround on color and material changes with polyolefins and their copolymers, styrenics polymers, acetals, vinyls, TPO, TPU, and many other resins processed in this temperature range. PURGEX 457 Plus can also be used on PVC purging applications and will neutralize HCl gasses.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Neutrex-Purgex-457-Purging-Compound.php

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 - 288 °C	300 - 550 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China