

Nitriflex Nitrilatex LVP- 106 Vinyl Pyridine Styrene Butadiene Latex

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

NITRILATEX synthetic lattices are divided into several groups, modified or not with carboxylic acid. Applications: NITRILATEX synthetic lattices are specially indicated to impregnate cords, adhesives manufacture, fibers agglomeration, supported gloves manufacture, impregnation of non-woven, etc. Information provided by Dax Resinas

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nitriflex-Nitrilatex-LVP-106-Vinyl-Pyridine-Styrene-Butadiene-Latex.php

Physical Properties	Metric	English	Comments
Solids Content	40 - 42 %	40 - 42 %	Method L-001/P-065; ASTM D1417
pH	10 - 11	10 - 11	25°C, Method L-003; ASTM D1417
Brookfield Viscosity	45 - 54 cP	45 - 54 cP	(spindle=1, 20 rpm); ASTM D1417
Mooney Viscosity	30 - 45	30 - 45	Method L-015; ASTM D1417, ASTM D1646
Surface Tension	46 - 55 dynes/cm	46 - 55 dynes/cm	Method L-005/L-040; ASTM D1417

Descriptive Properties	Value	Comments
Appearance	Purple Liquid	
Coagulum Content %	0-0.05	ASTM D1417; Method L-004
Cream Content g/150ml	0-0.03	Method L-013
Vinyl Pyridine Content g/150ml	13-15	ASTM D3533; Method B-016/B-028

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China