

## Nitriflex Nitrilatex NTL-218 Carboxylated Styrene Butadiene Latex

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

### Material Notes:

NITRILATEX synthetic lattices are divided into several groups, modified or not with carboxylic acid. Applications: NITRILATEX synthetic lattices are specially indicated to impregnate cords, adhesives manufacture, fibers agglomeration, supported gloves manufacture, impregnation of non-woven, etc. Information provided by Dax Resinas

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Nitriflex-Nitrilatex-NTL-218-Carboxylated-Styrene-Butadiene-Latex.php](http://www.lookpolymers.com/polymer_Nitriflex-Nitrilatex-NTL-218-Carboxylated-Styrene-Butadiene-Latex.php)

Physical Properties	Metric	English	Comments
Solids Content	48 - 50 %	48 - 50 %	Method L-001/P-065; ASTM D1417
pH	8.5 - 9.5	8.5 - 9.5	25°C, Method L-003; ASTM D1417
Brookfield Viscosity	90 - 200 cP	90 - 200 cP	(spindle=1, 20 rpm); ASTM D1417
Surface Tension	40 - 50 dynes/cm	40 - 50 dynes/cm	Method L-005/L-040; ASTM D1417

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China