

Nitriflex Nitrilatex NTL-350 Styrene Butadiene Latex

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

NITRILATEX synthetic lattices are divided into several groups, modified or not with carboxylic acid. Applications: NITRILATEX synthetic lattices are specially indicated to impregnate cords, adhesives manufacture, fibers agglomeration, supported gloves manufacture, impregnation of non-woven, etc. Information provided by Dax Resinas

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nitriflex-Nitrilatex-NTL-350-Styrene-Butadiene-Latex.php

| Physical Properties | Metric | English | Comments |
|----------------------|------------------|------------------|---------------------------------|
| Solids Content | 49 - 51 % | 49 - 51 % | Method L-001/P-065; ASTM D1417 |
| pH | 11 - 12 | 11 - 12 | 25°C, Method L-003; ASTM D1417 |
| Brookfield Viscosity | 70 cP | 70 cP | (spindle=1, 20 rpm); ASTM D1417 |
| Surface Tension | 35 - 45 dynes/cm | 35 - 45 dynes/cm | Method L-005/L-040; ASTM D1417 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China