

Nye Lubricants 181B (SO) Synthetic Oil

Category : Fluid , Lubricant , Polyalphaolefin (PAO)

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-181B-SO-Synthetic-Oil.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|---------|---------|---|
| Viscosity Measurement | 131 | 131 | Viscosity Index of Base Oil; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F) | 61 cSt | 61 cSt | Base Oil; ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 9.5 cSt | 9.5 cSt | Base Oil; ASTM D445 |
| Evaporation Loss | 3.7 % | 3.7 % | 6.5 hrs, 200C; ASTM D972 |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|--------------------|
| Maximum Service Temperature, Air | 125 °C | 257 °F | Recommended |
| Minimum Service Temperature, Air | -40.0 °C | -40.0 °F | Recommended |
| Pour Point | -57.0 °C | -70.6 °F | Base Oil; ASTM D97 |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| Base Fluid Type | PAO | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China