

Nye Lubricants 570H-25 (NT) Synthetic Oil

Category : Fluid , Lubricant , Perfluoropolyether (PFPE) , Silica Gellant

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-570H-25-NT-Synthetic-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	144	144	Viscosity Index of Base Oil; ASTM D2270
Kinematic Viscosity at 40°C (104°F)	500 cSt	500 cSt	Base Oil; ASTM D445
Kinematic Viscosity at 100°C (212°F)	43 cSt	43 cSt	Base Oil; ASTM D445
Evaporation Loss	1.0 %	1.0 %	6.5 hrs, 200C; ASTM D972

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	225 °C	437 °F	Recommended
Minimum Service Temperature, Air	-30.0 °C	-22.0 °F	Recommended
Pour Point	-28.0 °C	-18.4 °F	Base Oil; ASTM D97

Descriptive Properties	Value	Comments
Base Fluid Type	PFPE(pnd)	
Gellant Type	Silica(BL)	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China