

Nye Lubricants 708D (NG) Synthetic Oil

Category : Fluid , Lubricant , Clay Gellant , White Mineral Oil (WMO)

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-708D-NG-Synthetic-Oil.php

Physical Properties	Metric	English	Comments
Kinematic Viscosity at 100°C (212°F)	6.0 cSt	6.0 cSt	Base Oil; ASTM D445
Evaporation Loss	3.8 %	3.8 %	22 hrs, 100C; ASTM D972

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	290	290	ASTM D217
Penetration P(60), 1/10 mm	308	308	ASTM D217
Oil Separation	3.5 %	3.5 %	30 hrs, 100C; FTM 719B, 321.2

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	200 °C	392 °F	Recommended
Minimum Service Temperature, Air	-53.0 °C	-63.4 °F	Recommended

Descriptive Properties	Value	Comments
Base Fluid Type	wmo/poly	
Gellant Type	Clay	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China