

Nye Lubricants 718B (NG) Rheolube Grease

Category : Fluid , Lubricant , Polyphenylether (PPE) Base , Silica Gellant

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-718B-NG-Rheolube-Grease.php

Physical Properties	Metric	English	Comments
Kinematic Viscosity at 40°C (104°F)	363 cSt	363 cSt	Base Oil; ASTM D445
Kinematic Viscosity at 100°C (212°F)	13 cSt	13 cSt	Base Oil; ASTM D445
Evaporation Loss	0.00 %	0.00 %	24 hrs, 150C; ASTM D972

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	191	191	ASTM D217
Oil Separation	1.0 %	1.0 %	24 hrs, 150C; FTM 719B, 321.2

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	Recommended
Minimum Service Temperature, Air	4.00 °C	39.2 °F	Recommended
Pour Point	4.00 °C	39.2 °F	Base Oil; ASTM D97

Descriptive Properties	Value	Comments
Base Fluid Type	PPE	
Gellant Type	Silica (WL)	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China