

Nye Lubricants 774L-UV (NG) Synthetic Oil

Category : Fluid , Lubricant , Polyalphaolefin (PAO) , Silica Gellant

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-774L-UV-NG-Synthetic-Oil.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|----------|----------|---|
| Viscosity Measurement | 251 | 251 | Viscosity Index of Base Oil; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F) | 2054 cSt | 2054 cSt | Base Oil; ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 230 cSt | 230 cSt | Base Oil; ASTM D445 |
| Evaporation Loss | 0.20 % | 0.20 % | 24 hrs, 100C; ASTM D972 |

| Mechanical Properties | Metric | English | Comments |
|----------------------------|--------|---------|-------------------------------|
| Penetration P(0), 1/10 mm | 267 | 267 | ASTM D217 |
| Penetration P(60), 1/10 mm | 287 | 287 | ASTM D217 |
| Oil Separation | 1.3 % | 1.3 % | 24 hrs, 100C; FTM 719B, 321.2 |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|--------------------|
| Maximum Service Temperature, Air | 120 °C | 248 °F | Recommended |
| Minimum Service Temperature, Air | -40.0 °C | -40.0 °F | Recommended |
| Pour Point | -37.0 °C | -34.6 °F | Base Oil; ASTM D97 |

| Descriptive Properties | Value | Comments |
|------------------------|-------------|----------|
| Base Fluid Type | PAO | |
| Gellant Type | Silica (WL) | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China