

Nye Lubricants UniFlor 8110 (UF) Synthetic Oil

Category : Fluid , Lubricant , Perfluoropolyether (PFPE)

Material Notes:

Information provided by Nye Lubricants.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nye-Lubricants-UniFlor-8110-UF-Synthetic-Oil.php

| Physical Properties | Metric | English | Comments |
|--------------------------------------|---------|---------|---|
| Viscosity Measurement | 105 | 105 | Viscosity Index of Base Oil; ASTM D2270 |
| Kinematic Viscosity at 40°C (104°F) | 25 cSt | 25 cSt | Base Oil; ASTM D445 |
| Kinematic Viscosity at 100°C (212°F) | 4.7 cSt | 4.7 cSt | Base Oil; ASTM D445 |
| Evaporation Loss | 25 % | 25 % | 24 hrs, 150C; ASTM D972 |

| Thermal Properties | Metric | English | Comments |
|----------------------------------|----------|----------|--------------------|
| Maximum Service Temperature, Air | 125 °C | 257 °F | Recommended |
| Minimum Service Temperature, Air | -54.0 °C | -65.2 °F | Recommended |
| Pour Point | -56.0 °C | -68.8 °F | Base Oil; ASTM D97 |

| Descriptive Properties | Value | Comments |
|------------------------|-----------|----------|
| Base Fluid Type | PFPE(pnd) | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China