

Nylene® 615 Nylon 6, Film Grade

Category : Polymer , Film , Thermoplastic , Nylon , Nylon 6 , Nylon 6, Film Grade

Material Notes:

Film Grade. Nylene 615 is an extrusion grade nylon 6 resin suitable for coating and film co-extrusion applications. It has excellent melt stability and good melt strength. Nylene 615 has superior grease resistance, toughness, resistance to abrasion, and does not absorb food odors. Nylene 15 meets the requirements of FDA regulation 21 CFR 177.1500 for direct food contact.ALM, Nylene Canada, and Custom Resins are all operting companies of Polymeric Resources Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nylene-615-Nylon-6-Film-Grade.php

| Physical Properties | Metric | English | Comments |
|---------------------|-----------|---------------------------|-----------|
| Density | 1.12 g/cc | 0.0405 lb/in ³ | ASTM D792 |

| Mechanical Properties | Metric | English | Comments |
|------------------------------------|-----------|----------|--|
| Film Tensile Strength at Yield, MD | 38.0 MPa | 5510 psi | Orientation not specified; ASTM D882 |
| Film Elongation at Break, MD | 290 % | 290 % | Orientation not specified; ASTM D882 |
| Secant Modulus | 0.650 GPa | 94.3 ksi | ASTM D882 |
| Elmendorf Tear Strength MD | 56 g | 56 g | Orientation not specified; ASTM D1922 |
| Film Tensile Strength at Break, MD | 60.0 MPa | 8700 psi | Orientation not specified; ASTM D882 |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China