

Nylene® 9110 G33 , 33% Glass Reinforced Nylon 6/10

Category : Polymer , Thermoplastic , Nylon , Nylon 610 , Nylon 610, Glass Reinforced

Material Notes:

Description: Nylene® 9110 G33 is a 33% glass fiber reinforced nylon 6/10. Information provided by Custom Resins. ALM, Nylene Canada, and Custom Resins are all operating companies of Polymeric Resources Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Nylene-9110-G33-33-Glass-Reinforced-Nylon-610.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.32 g/cc	1.32 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	145 MPa	21000 psi	ASTM D638
Elongation at Break	25 %	25 %	ASTM D638
Flexural Modulus	7.58 GPa	1100 ksi	ASTM D790
Izod Impact, Notched	1.33 J/cm	2.50 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	214 °C	418 °F	ASTM D3418
Deflection Temperature at 1.8 MPa (264 psi)	196 °C	385 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China