

## Nylene® Vexel™ B12GF15 SA , 15% Glass Reinforced PBT

Category : Polymer , Thermoplastic , Polyester, TP , Polybutylene Terephthalate (PBT) , Polybutylene Terephthalate (PBT), 20% Glass Fiber Filled

### Material Notes:

Description: Vexel™ B12GF15 SA is a 15% glass fiber reinforced PBT with improved surface aPolyphenylene Etherarance. Information provided by Custom Resins. ALM, Nylene Canada, and Custom Resins are all operating companies of Polymeric Resources Corporation.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Nylene-Vexel-B12GF15-SA-15-Glass-Reinforced-PBT.php](http://www.lookpolymers.com/polymer_Nylene-Vexel-B12GF15-SA-15-Glass-Reinforced-PBT.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.41 g/cc	1.41 g/cc	ASTM D792
Linear Mold Shrinkage	0.0040 - 0.0080 cm/cm	0.0040 - 0.0080 in/in	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Ultimate	93.1 MPa	13500 psi	ASTM D638
Flexural Modulus	4.83 GPa	700 ksi	ASTM D790
Izod Impact, Notched	0.534 J/cm	1.00 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Melting Point	227 °C	440 °F	ASTM D3418
Deflection Temperature at 0.46 MPa (66 psi)	210 °C	410 °F	ASTM D648
Deflection Temperature at 1.8 MPa (264 psi)	191 °C	375 °F	ASTM D648

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China