

Oceanchem Group Antioxidant 1024

Category : Other Engineering Material , Additive/Filler for Polymer

Material Notes:

Molecular Formula: C₃₄H₅₂N₂O₄ Uses: Dosage is 0.1-0.5 portions. It is a metal deactivator, can work with antioxidant, used in PE, PP, polystyrene, polyamnamee, polyester, or used as antioxidant of bakelite, wire and cable. Storage and Packing: Stored in a dark and dry place in room temperature, plastic bag lined carton. Information Provided by Oceanchem Group

Order this product through the following link:

http://www.lookpolymers.com/polymer_Oceanchem-Group-Antioxidant-1024.php

Physical Properties	Metric	English	Comments
Volatiles	<= 0.50 %	<= 0.50 %	
Molecular Weight	553 g/mol	553 g/mol	
Ash	<= 0.10 %	<= 0.10 %	

Thermal Properties	Metric	English	Comments
Melting Point	224 - 229 °C	435 - 444 °F	

Optical Properties	Metric	English	Comments
Transmission, Visible	96 %	96 %	toluene solution
	@Wavelength 425 nm	@Wavelength 425 nm	
	98 %	98 %	toluene solution
	@Wavelength 500 nm	@Wavelength 500 nm	

Descriptive Properties	Value	Comments
Appearance	White crystalline powder	
Assay (%)	>99	
Molecular Formula	C ₃₄ H ₅₂ N ₂ O ₄	
Solubility	0.1	toluene (25°C, Wt)

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China