

## Ovation Polymers Nemcon™ E ABS 20CF

Category: Polymer, Thermoplastic, ABS Polymer

## **Material Notes:**

Nemcon E-series products are designed for use in ESDA electronic assembly environments where strict control of ESD and cleanliness are critical. Nemcon E ABS 20CF is a high modulus carbon fiber-reinforced ABS with excellent conductivity. It is suitable for a wide variety of injection molding applications, including electronic components, shipping trays, storage racks, electronic housings and work surfaces. Information provided by Ovation Polymers

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Ovation-Polymers-Nemcon-E-ABS-20CF.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.129 g/cc	1.129 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments	
Tensile Strength at Break	95.0 MPa	13800 psi	50 mm/min; ASTM D638	
Elongation at Break	1.9 %	1.9 %	50 mm/min; ASTM D638	
Tensile Modulus	10.5 GPa	1520 ksi	50 mm/min; ASTM D638	
Flexural Yield Strength	128 MPa	18600 psi	1.3 mm/min; ASTM D790	
Flexural Modulus	9.535 GPa	1383 ksi	1.3 mm/min; ASTM D790	
Izod Impact, Notched	0.459 J/cm	0.860 ft-lb/in	ASTM D256	
	@Temperature 23.0 °C	@Temperature 73.4 °F	701111220	

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	98.0 °C	208 °F	unannealed; ASTM D648
	@Thickness 3.20 mm	@Thickness 0.126 in	

Electrical Properties	Metric	English	Comments
Surface Resistivity per Square	2750 ohm	2750 ohm	ASTM D257

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China