

P & P Technology MW Series Conductive Fabric

Category : Metal , Nonferrous Metal , Copper Alloy , Nickel Alloy , Polymer , Thermoplastic , Nylon , Polyester, TP , Polyethylene Terephthalate (PET)

Material Notes:

Material: Nylon/PET/Nickel/Copper fabric Self Adhesive Tape: Conductive double sided acrylic carrier and adhesive information provided by P & P Technology

Order this product through the following link:

http://www.lookpolymers.com/polymer_P-P-Technology-MW-Series-Conductive-Fabric.php

Mechanical Properties	Metric	English	Comments
Abrasion	5000	5000	[cycles], No degradation after

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	70.0 °C	158 °F	
Minimum Service Temperature, Air	-20.0 °C	-4.00 °F	
Flammability, UL94	V-0	V-0	

Electrical Properties	Metric	English	Comments
Surface Resistance	<= 0.30 ohm	<= 0.30 ohm	
Shielding Effectiveness	65 dB @Frequency 1.00e+7 - 3.00e+9 Hz	65 dB @Frequency 1.00e+7 - 3.00e+9 Hz	

Descriptive Properties	Value	Comments
Color	Mid Grey	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China