

Pacific Sintered Materials FX-233-T(HT) Infiltrated Alloy Steel

Category : Metal , Ferrous Metal , Alloy Steel

Material Notes:

Excellent combination of strength and shock resistance. Good for use in cams, pawls, sprockets and wear plates. Moderate tolerance control. All information provided by Pacific Sintered Metals.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Pacific-Sintered-Materials-FX-233-THT-Infiltrated-Alloy-Steel.php

Physical Properties	Metric	English	Comments
Density	7.20 - 7.50 g/cc	0.260 - 0.271 lb/in ³	

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell C	46	46	
Tensile Strength, Ultimate	862 MPa	125000 psi	
Tensile Strength, Yield	862 MPa	125000 psi	
Elongation at Break	<= 0.50 %	<= 0.50 %	
Modulus of Elasticity	165 GPa	24000 ksi	
Charpy Impact, Unnotched	29.8 J	22.0 ft-lb	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China