

Permabond A905 Anaerobic Surface Activator

Category : Other Engineering Material , Catalyst/Initiator

Material Notes:

Permabond A Surface Activator (A905) is used in conjunction with Permabond A (anaerobic) adhesives and sealants. A905 is designed to allow non-metallic surfaces to be bonded/sealed. It also accelerates the cure rate of anaerobics and improves bonding to contaminated surfaces. It will also allow the adhesive to cure in a larger gap. Features & Benefits: Liquid or spray Quick & easy to use Activates non-metallic and low-reactivity surfaces Improves adhesive gap fill Information provided by Permabond.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Permabond-A905-Anaerobic-Surface-Activator.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.700 g/cc	0.700 g/cc	Uncured
Viscosity	0.55 cP	0.55 cP	Uncured
Evaporation Loss	7.7 %	7.7 %	
Storage Temperature	5.00 - 25.0 °C	41.0 - 77.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	63.0 °C	145 °F	
Flash Point	-26.0 °C	-14.8 °F	

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Appearance	Green	Uncured

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China