

Permabond CSA Cyanoacrylate Surface Activator

Category : Other Engineering Material , Catalyst/Initiator

Material Notes:

Permabond C Surface Activator (CSA) is used in conjunction with Permabond cyanoacrylate adhesives to promote a faster cure and to extend their gap-filling capabilities. It also enables fillets of cured adhesive to be formed if required and can be used to reduce the effects of blooming, which can affect decorative surfaces. Use of CSA also facilitates the bonding of porous surfaces. Permabond CSA can be supplied either as an aerosol spray, for ease of application, or as a bulk liquid for use in high volume applications. Features& Benefits: Liquid or spray Quick and Easy to use Activates difficult or porous surfaces Improves adhesive gap fill Information provided by Permabond.

Order this product through the following link: http://www.lookpolymers.com/polymer_Permabond-CSA-Cyanoacrylate-Surface-Activator.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.700 g/cc	0.700 g/cc	Uncured
Viscosity	0.55 cP	0.55 cP	
Evaporation Loss	7.7 %	7.7 %	
Storage Temperature	5.00 - 25.0 °C	41.0 - 77.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	102 °C	216 °F	
Flash Point	-7.00 °C	19.4 °F	

Processing Properties	Metric	English	Comments
Shelf Life	24.0 Month	24.0 Month	

Descriptive Properties	Value	Comments
Appearance	Colorless	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China