

Permabond POP Polyolefin Primer

Category : Fluid , Lubricant

Material Notes:

Permabond® Polyolefin Primer has been developed for surface treatment of polyolefins, PTFE and silicones prior to bonding with Permabond® Cyanoacrylate adhesives. Due to their low surface energy, plastics such as PTFE, Polypropylene (PP), Polyethylene (PS) and Silicones are difficult to bond without special surface treatment. However, after treatment with Permabond® Polyolefin Primer, durable bonds stronger than the substrate material can be achieved. Information provided by Permabond.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Permabond-POP-Polyolefin-Primer.php

Physical Properties	Metric	English	Comments
Density	0.680 g/cc	0.0246 lb/in ³	
Viscosity	0.60 cP @Temperature 25.0 °C	0.60 cP @Temperature 77.0 °F	
Evaporation Loss	2.8 %	2.8 %	
Storage Temperature	5.00 - 25.0 °C	41.0 - 77.0 °F	

Thermal Properties	Metric	English	Comments
Boiling Point	98.0 °C	208 °F	
Flash Point	-4.00 °C	24.8 °F	

Processing Properties	Metric	English	Comments
Cure Time	0.500 min @Temperature 23.0 °C	0.00833 hour @Temperature 73.4 °F	Drying Time
Shelf Life	12.0 Month	12.0 Month	

Descriptive Properties	Value	Comments
Appearance	Colorless	
UV Fluorescence	Yes	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China