

## Phillips 66 COPYLENE® CH350V Polypropylene, Homopolymer, Extrusion Coating, Spunbound, Gas Fade & UV Resistant

Category : Polymer , Thermoplastic , Polypropylene (PP)

### Material Notes:

COPYLENE™ CH350V is a very high melt flow polypropylene homopolymer resin designed for fiber spinning. Applications: Food Packaging Film, Heavy Duty Packaging, Absorption & Filtration, Filament Yarn, Furniture & Buildings, IBCs, Geotextile & Agriculture, Hygiene Nonwoven, Protective Clothes, Wipes/Tissues. Equivalent to Pro-fax® HL344S Information provided by Phillips 66.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Phillips-66-COPYLENE-CH350V-Polypropylene-Homopolymer-Extrusion-Coating-Spunbound-Gas-Fade-UV-Resistant.php](http://www.lookpolymers.com/polymer_Phillips-66-COPYLENE-CH350V-Polypropylene-Homopolymer-Extrusion-Coating-Spunbound-Gas-Fade-UV-Resistant.php)

Physical Properties	Metric	English	Comments
Density	0.902 g/cc	0.0326 lb/in <sup>3</sup>	ASTM D792
Melt Flow	35 g/10 min @Load 2.16 kg, Temperature 230 °C	35 g/10 min @Load 4.76 lb, Temperature 446 °F	ASTM D1238

Descriptive Properties	Value	Comments
Process	Fiber	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China