

Plastics Group Polifil® RMC-10 10% Calcium Carbonate-Reinforced Polypropylene, High Impact

Category : Polymer , Thermoplastic , Polypropylene (PP) , Polypropylene with 10% Calcium Carbonate (CaCO₃) Filler

Material Notes:

Polifil® RMC series compounds are high impact polypropylenes reinforced with fine particle size calcium carbonate. In addition to the highest impact possible, they possess good stiffness, heat aging resistance, solvent resistance, surface quality, and good resistance to environmental stress-cracking. Applications: Automotive Appliances Electrical components Housewares Various utility products Standard processing techniques are applicable. Information provided by The Plastics Group.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Plastics-Group-Polifil-RMC-10-10-Calcium-Carbonate-Reinforced-Polypropylene-High-Impact.php

Physical Properties	Metric	English	Comments
Density	0.980 g/cc	0.0354 lb/in ³	ASTM D792
Filler Content	10 %	10 %	ASTM D2584
Linear Mold Shrinkage	0.014 cm/cm @Thickness 1.59 mm	0.014 in/in @Thickness 0.0625 in	ASTM D955
Melt Flow	8.0 - 12 g/10 min	8.0 - 12 g/10 min	230/2.16; May be specified; ASTM D1238

Mechanical Properties	Metric	English	Comments
Hardness, Rockwell R	86	86	ASTM D785
Tensile Strength at Break	24.8 MPa	3600 psi	ASTM D638
Flexural Modulus	1.48 GPa	215 ksi	Tangent; ASTM D790
Izod Impact, Notched	0.854 J/cm	1.60 ft-lb/in	At 73°F; ASTM D256
Izod Impact, Unnotched	10.7 J/cm	20.0 ft-lb/in	At 73°F; ASTM D256
Gardner Impact	7.46 J	5.50 ft-lb	ASTM D3029

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	99.4 °C	211 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China