

PlastxWorld CEVIAN® EG106 ABS

Category : Polymer , Thermoplastic , ABS Polymer

Material Notes:

Inherently Static Dissipative and Glass Fiber reinforced ABS. These are typical values and are not intended for specification purposes. UL approved file No. is E47773. Information provided by PlastxWorld Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_PlastxWorld-CEVIAN-EG106-ABS.php

Physical Properties	Metric	English	Comments
Density	1.28 g/cc	0.0462 lb/in ³	ASTM D792
Linear Mold Shrinkage	0.0010 - 0.0030 cm/cm	0.0010 - 0.0030 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	81.4 MPa	11800 psi	ASTM D638
Flexural Yield Strength	106 MPa	15400 psi	ASTM D790
Flexural Modulus	5.98 GPa	868 ksi	ASTM D790
Izod Impact, Notched	1.01 J/cm @Thickness 3.17 mm	1.90 ft-lb/in @Thickness 0.125 in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	105 °C	221 °F	0.5 inch; ASTM D648
Flammability, UL94	HB	HB	

Electrical Properties	Metric	English	Comments
Surface Resistance	3.00e+11 ohm	3.00e+11 ohm	ASTM D249

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China