

## PolyChem Alloy PolyFoam DCE5

Category : Polymer

### Material Notes:

PolyFoam decomposes when heated to create a uniform microcellular structure. It can be used in extrusion and injection molding processes to reduce weight in parts without adversely affecting the physical properties. Other benefits include the elimination of sink marks and an improved surface quality. For foamed extrusions, PolyFoam used in combination with a gas blowing agent improves the efficiency of the physical agent, reducing of gas usage, part weight, and often scrap. PolyFoam products come in a uniform pelletized shape and are available with endothermic blowing agents, exothermic blowing agents, or both.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_PolyChem-Alloy-PolyFoam-DCE5.php](http://www.lookpolymers.com/polymer_PolyChem-Alloy-PolyFoam-DCE5.php)

Processing Properties	Metric	English	Comments
Processing Temperature	190 - 230 °C	374 - 446 °F	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China