

## PolyOne Aquamix™ 568 Latex

Category : Other Engineering Material , Additive/Filler for Polymer

### Material Notes:

**Storage Stability:** In excess of 6 months when stored under proper conditions in original sealed container. Keep from freezing. Water lost by evaporation can adversely affect viscosity, dispersability, and other physical properties. Any soft settling may be removed by stirring.

Copies of PolyOne test methods are available upon customer request. Information provided by PolyOne

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_PolyOne-Aquamix-568-Latex.php](http://www.lookpolymers.com/polymer_PolyOne-Aquamix-568-Latex.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.05 g/cc	1.05 g/cc	Liquid
Solids Content	51 - 53 % @Temperature 105 °C	51 - 53 % @Temperature 221 °F	
Particle Size	<= 5.0 µm	<= 5.0 µm	
pH	8.0 - 10	8.0 - 10	
Brookfield Viscosity	400 - 1000 cP	400 - 1000 cP	RVF #3, 10 rpm, 424

Descriptive Properties	Value	Comments
Active Ingredient	Polypale Ester 10 BHT with ~softening point 109°C	
Binder/Vehicle	Water	
Forms	Pellets	
Generic Material	Latex	
Generic Name	Latex	
Regional Availability	North America	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China