

PolyOne Geon™ Vinyl Flexible 90253 Polyvinyl Chloride, Flexible (PVC, Flexible)

Category : Polymer , Thermoplastic , Vinyl (PVC)

Material Notes:

Information provided by PolyOne

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyOne-Geon-Vinyl-Flexible-90253-Polyvinyl-Chloride-Flexible-PVC-Flexible.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.32 g/cc	1.32 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	85	85	15 sec; ASTM D2240
	90	90	ASTM D2240
Tensile Strength at Break	17.6 MPa	2550 psi	Type IV, 510 mm/min; ASTM D638
Tensile Strength	10.6 MPa @Strain 100 %	1540 psi @Strain 100 %	Type IV, 510 mm/min; ASTM D638
Elongation at Break	350 %	350 %	Type IV, 510 mm/min; ASTM D638
Tear Strength	77.0 kN/m	439 pli	Die C, 2 in/min; ASTM D1004

Thermal Properties	Metric	English	Comments
Brittleness Temperature	-26.0 °C	-14.8 °F	ASTM D746

Descriptive Properties	Value	Comments
Features	General Purpose	
Forms	Pellets	
Generic Material	PVC, Flexible	
Generic Name	Polyvinyl Chloride, Flexible (PVC, Flexible)	
Processing Method	Extrusion	
	Injection Molding	
Regional Availability	Africa & Middle East	
	Asia Pacific	
	Europe	

Descriptive Properties	Value	Comments
	North America	
	South America	
Uses	Automotive Applications	
	Gaskets	
	General Purpose	
	Protective Coverings	
	Seals	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China