

PolyOne Synprene® RT-3620 Thermoplastic Elastomer - SBC (discontinued **)

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE

Material Notes:

Description/Features:Multi-Purpose Thermoplastic ElastomerNaturalApplications:General PurposeInteriorMarket:Consumer GoodsIndustrialProcessing Method:Injection MoldingPolyOne First ChoiceInformation provided by PolyOne Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyOne-Synprene-RT-3620-Thermoplastic-Elastomer-SBC-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.00 g/cc	1.00 g/cc	ASTM D792
Linear Mold Shrinkage	0.010 cm/cm	0.010 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	20	20	Instant; ASTM D2240
Tensile Strength, Yield	2.55 MPa	370 psi	Method A (Dumbbell & Section), 20 in/min, Break; ASTM D412
	0.931 MPa @Strain 300 %	135 psi @Strain 300 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
Elongation at Break	730 %	730 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
Tear Strength	10.5 kN/m	60.0 pli	Die C (graves), 20 in/min; ASTM D624
Compression Set	12 %	12 %	Method B, 73°F(23°C), 22 hrs; ASTM D395

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China