

PolyOne Synprene® RT-4070 Thermoplastic Elastomer - SBC, Mineral Filled (discontinued **)

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE

Material Notes:

Description/Features:Multi-Purpose Thermoplastic ElastomerMineral FilledApplications:Multi-PurposeMarket:AutomotiveBuilding and ConstructionIndustrialConsumer GoodsProcessing Method:ExtrusionInformation provided by PolyOne Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyOne-Synprene-RT-4070-Thermoplastic-Elastomer-SBC-Mineral-Filled-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.16 g/cc	1.16 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	72	72	Instant; ASTM D2240
Tensile Strength, Yield	7.93 MPa	1150 psi	Method A (Dumbbell & Section), 20 in/min, Break; ASTM D412
	4.83 MPa @Strain 300 %	700 psi @Strain 300 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
Elongation at Break	650 %	650 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
Tear Strength	30.7 kN/m	175 pli	Die C (graves), 20 in/min; ASTM D624
Compression Set	22 %	22 %	Method B, 73°F(23°C), 22 hrs; ASTM D395

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China