

PolyOne Synprene® ST-6240 Thermoplastic Elastomer - SBC (discontinued **)

Category : Polymer , Thermoplastic , Elastomer, TPE , Styrenic TPE

Material Notes:

Description/Features:Over-Molding GradeUV StabilizedApplications:Multi-PurposeProcessing Method:Injection MoldingPolyOne First ChoiceInformation provided by PolyOne Corporation.

Order this product through the following link:

http://www.lookpolymers.com/polymer_PolyOne-Synprene-ST-6240-Thermoplastic-Elastomer-SBC-nbspdiscontinued-.php

Physical Properties	Metric	English	Comments
Specific Gravity	0.960 g/cc	0.960 g/cc	ASTM D792
Linear Mold Shrinkage	0.020 cm/cm	0.020 in/in	ASTM D955

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	43	43	5 sec; ASTM D2240
Tensile Strength, Yield	7.65 MPa	1110 psi	Method A (Dumbbell & Section), 20 in/min, Break; ASTM D412
	1.86 MPa @Strain 100 %	270 psi @Strain 100 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
	3.72 MPa @Strain 300 %	540 psi @Strain 300 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
Elongation at Break	740 %	740 %	Method A (Dumbbell & Section), 20 in/min; ASTM D412
Tear Strength	29.8 kN/m	170 pli	Die C (graves), 20 in/min; ASTM D624

Contact Songhan Plastic Technology Co.,Ltd.Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China