

Polymax® Maxelast® F02-081A-10C TPE, Halogen Free Extrusion Grade

Category : Polymer , Thermoplastic , Elastomer, TPE

Material Notes:

Characteristics: Good melt strengthSoft touchSmooth surface with dry feelGood weather and heat resistanceWide range of hardnessEasy processing Halogen FreeLow smoke emissionRoHs compliantDesigned to meet UL 94 V0Excellent weathering and UV resistanceGood chemical resistanceEasy processing
Typical Applications: Electrical and Electronics, Wire and CableIndustrial
Information from Alliance
Polymers & Services, Distributor of Nantong Elastomer Technology Co.Ltd

Order this product through the following link:

http://www.lookpolymers.com/polymer_Polymax-Maxelast-F02-081A-10C-TPE-Halogen-Free-Extrusion-Grade.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.16 g/cc	1.16 g/cc	ASTM D792

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	85	85	ASTM D2240
Tensile Stress	6.17 MPa	895 psi	ASTM D412
	@Strain 100 %	@Strain 100 %	
Tensile Strength, Yield	7.10 MPa	1030 psi	ASTM D412
	@Strain 300 %	@Strain 300 %	
Elongation at Break	470 %	470 %	ASTM D412

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China