

Precision Polymer Engineering E70Z Ethylene Propylene Rubber

Category : Polymer , Thermoset , Rubber or Thermoset Elastomer (TSE)

Material Notes:

Peroxide cured, grey Ethylene Propylene Terpolymer, 65-75 °IRHD. Terpolymer of ethylene, propylene and diene monomers. Specially formulated for sealing applications involving high voltage electrical equipment. Applications: Compound designed specially for sealing SF6 gas in electrical distribution equipment, i.e. medium & high voltage switchgear at low temperatures. The specially selected fillers used in this compound impart excellent electrical non-conductive properties to the rubber.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Precision-Polymer-Engineering-E70Z-Ethylene-Propylene-Rubber.php

Mechanical Properties	Metric	English	Comments
Hardness, Shore A	70	70	°IRHD; ASTM D1415
	74	74	°IRHD, +4 change after 70 hours @ 150°C; ASTM D1415
Tensile Strength, Yield	5.00 MPa	725 psi	ASTM D412
Elongation at Break	241 %	241 %	ASTM D412
Compression Set	10.4 %	10.4 %	72 hours @ 100°C; ASTM D395

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	150 °C	302 °F	
Minimum Service Temperature, Air	-50.0 °C	-58.0 °F	
	-48.0 °C	-54.4 °F	Non-brittle after 3 minutes
Flash Point	>= 200 °C	>= 392 °F	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China