

Premix Thermoplastics PREADD SL 502

Category: Polymer, Thermoplastic, Polypropylene (PP)

Material Notes:

PREADD SL 502 is a polypropylene based slip masterbatch developed for cast-PP and BOPP films.PREADD SL 502 contains highly purified erucamide, which is neutral in odor and color. PREADD SL 502 does not give problems in printing, heat sealing or bonding unless overdosed. PREADD SL 502 is approved for use in contact with foodstuffs according to FDA regulations without limitations and according to BgVV regulations as long as the dosage level of PREADD SL 502 is less than 4 %.Information provided by Premix Thermoplastics Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Premix-Thermoplastics-PREADD-SL-502.php

Physical Properties	Metric	English	Comments
Density	0.900 g/cc	0.0325 lb/in³	
Additive Loading	5.0 %	5.0 %	Erucamide

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 °C	500 °F	

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.25 %	<= 0.25 %	When Produced
Shelf Life	12.0 Month	12.0 Month	Normal Storing Conditions

Descriptive Properties	Value	Comments
Appearance	Granule	
Carrier	PP Homo Polymer	
Color	Transparent	
Dosing, %	0.5 to 4	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China