

## **Premix Thermoplastics PREBLACK PE 700-40**

Category: Polymer, Thermoplastic, Polyethylene (PE)

## **Material Notes:**

PREBLACK PE 700-40 is a polyethylene based black masterbatch. PREBLACK PE 700-40 has been developed for the coloring of PE-LD and PE-HD products when maximum UV-resistance and pureness is being required. The moisture absorption and sulphur content of PREBLACK PE 700-40 are very low preventing odor problems. According to BgVV regulations PREBLACK PE 700-40 is approved for use in contact with foodstuffs as long as the content of carbon black in the produced product is less than 2.5%. Information provided by Premix Thermoplastics Inc.

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Premix-Thermoplastics-PREBLACK-PE-700-40.php

Physical Properties	Metric	English	Comments
Density	1.15 g/cc	0.0415 lb/in³	

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	300 °C	572 °F		

Processing Properties	Metric	English	Comments
Moisture Content	<= 0.15 %	<= 0.15 %	When Produced
Shelf Life	12.0 Month	12.0 Month	Normal Storing Conditions

Descriptive Properties	Value	Comments
Appearance	Granule	
Carrier	PE-LD	
Dosing, %	0.5 to 10	Depending on desired blackness and UV-protection
Light Fastness	8-Very Good	
Pigmentation, %	40	Special carbon black (p-type)

## Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China