

Protective Coating PC-Lumber™ Epoxy Putty

Category : Polymer , Adhesive , Thermoset , Epoxy , Epoxy Adhesive

Material Notes:

PC-PUTTIES™ are hand moldable epoxy putty that are especially designed for emergency type repairs where time is of the essence. Data provided by the manufacturer.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Protective-Coating-PC-Lumber-Epoxy-Putty.php

Physical Properties	Metric	English	Comments
Linear Mold Shrinkage	<= 0.010 cm/cm	<= 0.010 in/in	ASTM D2566

Mechanical Properties	Metric	English	Comments
Hardness, Shore D	80	80	1 Week Cure; ASTM D2240
Compressive Yield Strength	83.0 MPa	12000 psi	ASTM D695
Adhesive Bond Strength	3.40 MPa	493 psi	Tensile Shear Strength; ASTM D1002

Electrical Properties	Metric	English	Comments
Electrical Resistivity	3.00e+10 ohm-cm	3.00e+10 ohm-cm	ASTM D257
Dielectric Strength	12.0 kV/mm	305 kV/in	ASTM D149

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China