

Protective Coating PC-Petrifier® Wood Hardener

Category : Polymer , Adhesive , Thermoset , Epoxy , Epoxy Adhesive

Material Notes:

Description: PC-Petrifier® is great for sealing and restoring rotted soft wood fibers found in window sills, sashes, frames, trim, beams and columns, fences, decks, paneling, flooring, log homes, playground equipment, picnic tables, cellar doors, and planking (exposed end grain).

PC-Petrifier® can be used to prepare old wood for priming and painting. For structural wood repairs use PC Rot-Terminator® epoxy consolidant.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Protective-Coating-PC-Petrifier-Wood-Hardener.php

| Physical Properties | Metric | English | Comments |
|--|------------|------------|----------|
| Volatile Organic Compounds (VOC) Content | <= 125 g/l | <= 125 g/l | |

| Processing Properties | Metric | English | Comments |
|-----------------------|------------------|-----------------|---|
| Cure Time | 480 min | 8.00 hour | (overnight), For service (Depends on temperature and porosity of wood being treated). |
| | 4320 - 10100 min | 72.0 - 168 hour | Maximum Cure |

| Descriptive Properties | Value | Comments |
|------------------------|-------------------------------|----------|
| Color | Milky White | |
| Conduction (Electric) | Non Conductive | |
| Shelf Life | Min. 2 years | |
| Thermal Shock | Excellent | |
| Toxicity | Cured PC-Petrifier® Non Toxic | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China