

Pyrotek Fiberseal Paper C-3 Ceramic fiber paper

Category : Ceramic , Oxide , Aluminum Oxide , Silicon Oxide

Material Notes:

C-3 fiberseal paper is designed for applications where high temperature protection is required. C-3 is resistant to most chemicals with exception of hydrofluoric and phosphoric acids and strong alkalis. Applications Industrial gaskets Liquid metal back-up insulation Brazing furnace insulation Investment casting parting agent Advantages Resistant to most chemicals Thermal properties remain unaffected by exposure to water or steam Information provided by Pyrotek.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Pyrotek-Fiberseal-Paper-C-3-Ceramic-fiber-paper.php

Physical Properties	Metric	English	Comments
Density	0.192 - 0.224 g/cc	0.00694 - 0.00809 lb/in ³	
Binder	0.080 - 0.14	0.080 - 0.14	organic

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	1260 °C	2300 °F	

Component Elements Properties	Metric	English	Comments
Al ₂ O ₃	50 %	50 %	
SiO ₂	48 %	48 %	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China