

## Pyrotek Pyrite Vacuum Formed Product

Category : Ceramic

**Material Notes:**

Off White Color Applications Tap hole cones Riser sleeves Launder insulation Head boxes Ladle lining Pouring cups Advantages Good thermal shock resistance High strength/weight ratio Low thermal conductivity Non wetting Information provided by Pyrotek.

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Pyrotek-Pyrite-Vacuum-Formed-Product.php](http://www.lookpolymers.com/polymer_Pyrotek-Pyrite-Vacuum-Formed-Product.php)

Physical Properties	Metric	English	Comments
Density	0.250 g/cc	0.00903 lb/in <sup>3</sup>	

Thermal Properties	Metric	English	Comments
Melting Point	1760 °C	3200 °F	
Maximum Service Temperature, Air	1260 °C	2300 °F	
Shrinkage	4.00 % @Temperature 1260 °C, Time 86400 sec	4.00 % @Temperature 2300 °F, Time 24.0 hour	Linear

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China