

Quadrant EPP Symalit® 1000 ETFE unfilled, lining industries (ISO Data)

Category : Polymer , Thermoplastic , Fluoropolymer , ETFE/ECTFE , Fluorocarbon ETFE/ECTFE , Molded/Extruded

Material Notes:

Service temperature range from -190 °C up to +155 °C / -310 °F up to +311 °F Mechanical and technical features correspond to those of ECTFE Excellent weather proof and radiation proof Low water adsorption Excellent resistance of abrasion

Order this product through the following link:

http://www.lookpolymers.com/polymer_Quadrant-EPP-Symalit-1000-ETFE-unfilled-lining-industries-ISO-Data.php

Compliance Properties	Metric	English	Comments
3A-Dairy	No	No	
USP Class VI	No	No	

Chemical Resistance Properties	Metric	English	Comments
Acids, Strong (pH 1-3)	Acceptable	Acceptable	
Acids, Weak	Acceptable	Acceptable	
Alcohols	Acceptable	Acceptable	
Alkalies, Strong (pH 11-14)	Unacceptable	Unacceptable	
Alkalies, Weak	Limited	Limited	
Chlorinated Solvents	Limited	Limited	
Continuous Sunlight	Limited	Limited	
Hot Water / Steam	Acceptable	Acceptable	
Hydrocarbons - Aliphatic	Acceptable	Acceptable	
Hydrocarbons - Aromatic	Acceptable	Acceptable	
Inorganic Salt Solutions	Acceptable	Acceptable	
Ketones, Esters	Unacceptable	Unacceptable	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China