

Reliance Industries Repol H030SG Polypropylene

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene, Molded

Material Notes:

REPOL Polypropylene H030SG is manufactured using Unipol PP process which combines the production efficiency of gas phase fluidized bed reactor technology with the high activity stereospecific catalyst system. Repol H030SG is recommended for Raffia Tapes used in making woven fabrics for sacking, carpet backing, industrial packaging and geotextile applications. Features: High tenacity in tapes Consistent processability Low "water carryover" Good color and processing stability Information provided by Reliance Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_Reliance-Industries-Repol-H030SG-Polypropylene.php

Physical Properties	Metric	English	Comments
Melt Flow	3.0 g/10 min	3.0 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	35.0 MPa	5080 psi	50mm/min; ASTM D638
Elongation at Yield	10 %	10 %	50mm/min; ASTM D638
Flexural Modulus	1.65 GPa	239 ksi	1% secant; ASTM D790A
Izod Impact, Notched	0.400 J/cm	0.749 ft-lb/in	ASTM D256
	@Temperature 23.0 °C	@Temperature 73.4 °F	

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	104 °C	219 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China