

Reliance Industries Repol R110MK Polypropylene

Category: Polymer, Thermoplastic, Polypropylene (PP), Polypropylene, Molded

Material Notes:

REPOL Polypropylene R110MK is manufactured using Unipol PP process which combines the production efficiency of gas phase fluidized bed reactor technology with the high activity stereospecific catalyst system. Repol R110MK is recommended for use in injection molding processes. It is an ideal material for attaining high clarity in houseware and industrial products. This grade is recommended for non food contact applications. Repol R110MK contains clarifier and antistatic agent that reduces static charge buildup on products. Features:

Consistent processability Good claritySuperior mechanical propertiesLow static charge build-up and reduced dust pickupInformation provided by Reliance Industries

Order this product through the following link:

http://www.lookpolymers.com/polymer_Reliance-Industries-Repol-R110MK-Polypropylene.php

Physical Properties	Metric	English	Comments
Melt Flow	12 g/10 min	12 g/10 min	ASTM D1238
	@Load 2.16 kg, Temperature 230 °C	@Load 4.76 lb, Temperature 446 °F	

Mechanical Properties	Metric	English	Comments
Tensile Strength, Yield	28.0 MPa	4060 psi	50mm/min; ASTM D638
Elongation at Yield	12 %	12 %	50mm/min; ASTM D638
Flexural Modulus	1.30 GPa	189 ksi	1% secant; ASTM D790A
Izod Impact, Notched	0.600 J/cm	1.12 ft-lb/in	ASTM D256
1200 Impact, Notolica	@Temperature 23.0 °C	@Temperature 73.4 °F	

Thermal Properties	Metric	English	Comments
Melting Point	150 °C	302 °F	DSC second heating; ASTM D3418
Deflection Temperature at 0.46 MPa (66 psi)	95.0 °C	203 °F	ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China