

Reltek BONDiT™ B-45CC Adhesive and Sealant

Category : Polymer , Adhesive

Material Notes:

Key PropertiesExcellent adhesion to low surface energy plastics without primer. Caulking and sealing dissimilar materials for harsh environments. High impact resistance. Ease of use. **Applications**Caulks and seals difficult-to-bond substrates and dissimilar materials such as UHMW polyethylene and acetal (Delrin) to steel, wood, plastics, rubber, urethane and concrete. Survives harsh environments, particularly moisture, harsh chemical, marine and sub sea. Exceptional performance as a universal caulk for industrial applications. Will cure underwater. Can be applied to oily surfaces. Ambient 24 hour or accelerated thermal cure. Information provided by Reltek LLC

Order this product through the following link:

http://www.lookpolymers.com/polymer_Reltek-BONDiT-B-45CC-Adhesive-and-Sealant.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.05 g/cc	1.05 g/cc	A
	1.42 g/cc	1.42 g/cc	B

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China