

Reltek BONDiT™ B-46TH Adhesive and Sealant

Category : Polymer , Adhesive

Material Notes:

Key Properties Excellent adhesion to low surface energy plastics without primer or surface preparation. Applications Very high flexibility, 500% elongation, emphasizing high tack for un-abraded substrates and plastic films, including unetched Teflon. Excellent water and oil block for cable application. Ambient or thermal cure. May be catalyzed for fast set time. Information provided by Reltek LLC

Order this product through the following link:

http://www.lookpolymers.com/polymer_Reltek-BONDiT-B-46TH-Adhesive-and-Sealant.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.05 g/cc	1.05 g/cc	A
	1.42 g/cc	1.42 g/cc	B
Moisture Absorption at Equilibrium	<= 1.0 %	<= 1.0 %	
Viscosity	7000 cP	7000 cP	
	@Temperature 25.0 °C	@Temperature 77.0 °F	

Descriptive Properties	Value	Comments
Color	Clear with haze/slight amber	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China