

## **Resinlab® TL5042 Anaerobic Threadlocking Compound**

Category: Polymer, Adhesive

## **Material Notes:**

The TL5000 Series anaerobic threadlocking compounds are designed for use in demanding applications to fill the spaces and surface irregularities between tightly mated cylindrical parts. They form a tough permanent bonds which greatly enhances the torque and pullout strength. These products are highly resistant to heat, corrosion, vibration, water gases, oils and many other chemicals. They are single component solvent free materials manufactured in a wide variety of viscosities to satisfy specific bonding applications. This technology increases the reliability and performance of assemblies while reducing dependence upon maintaining costly tight machining tolerances. Information Provided by Resinlab L.L.C., an Ellsworth Adhesives Company.

## Order this product through the following link:

http://www.lookpolymers.com/polymer\_Resinlab-TL5042-Anaerobic-Threadlocking-Compound.php

Physical Properties	Metric	English	Comments
Specific Gravity	1.07 g/cc	1.07 g/cc	
Viscosity	1200 cP	1200 cP	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	350 °C	662 °F	
Minimum Service Temperature, Air	-60.0 °C	-76.0 °F	

Processing Properties	Metric	English	Comments
Cure Time	10.0 min	0.167 hour	Fixture
	480 min	8.00 hour	Full Cure

Descriptive Properties	Value	Comments
Color	Blue	
Thixotropy	Medium	
Torque (ft*lbs)	150	Breakaway Torque
	75	Prevailing Torque

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China