

SABIC Innovative Plastics LNP LUBRICOMP BX05030 SAN (Europe-Africa-Middle East)

Category : Polymer , Thermoplastic , SAN Polymer

Material Notes:

LNP* Lubricomp* BX05030 is a compound based on Styrene Acrylonitrile resin containing Mineral, Graphite.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-LUBRICOMP-BX05030-SAN-Europe-Africa-Middle-East.php

Physical Properties	Metric	English	Comments
Density	1.25 g/cc	0.0452 lb/in ³	ISO 1183
Linear Mold Shrinkage, Flow	0.0010 - 0.0040 cm/cm	0.0010 - 0.0040 in/in	on Tensile Bar; SABIC Method

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	50.0 MPa	7250 psi	5 mm/min; ISO 527
Elongation at Break	1.5 %	1.5 %	5 mm/min; ISO 527
Tensile Modulus	5.50 GPa	798 ksi	1 mm/min; ISO 527
Flexural Strength	75.0 MPa	10900 psi	2 mm/min; ISO 178
Flexural Modulus	4.80 GPa	696 ksi	2 mm/min; ISO 178
Izod Impact, Notched (ISO)	2.00 kJ/m ²	0.952 ft-lb/in ²	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	10.0 kJ/m ²	4.76 ft-lb/in ²	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	80.0 °C	176 °F	Flatw 80*10*4 sp=64mm; ISO 75/Af

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China