

SABIC Innovative Plastics LNP LUBRICOMP QFP36 PA 6/10 (Asia Pacific)

Category : Polymer , Thermoplastic , Nylon , Nylon 610

Material Notes:

LNP LUBRICOMP* QFP36 is a compound based on Nylon 6/10 resin containing Silicone, PTFE, Glass Fiber. Added features of this material include: Internally Lubricated.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-LUBRICOMP-QFP36-PA-610-Asia-Pacific.php

Physical Properties	Metric	English	Comments
Density	1.44 g/cc	0.0520 lb/in ³	ASTM D792
Linear Mold Shrinkage, Flow	0.0020 cm/cm @Time 86400 sec	0.0020 in/in @Time 24.0 hour	ASTM D955
Linear Mold Shrinkage, Transverse	0.0090 cm/cm @Time 86400 sec	0.0090 in/in @Time 24.0 hour	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	136 MPa	19700 psi	ASTM D638
Elongation at Break	2.8 %	2.8 %	ASTM D638
Flexural Strength	212 MPa	30700 psi	ASTM D790
Flexural Modulus	8.61 GPa	1250 ksi	ASTM D790
Izod Impact, Notched	0.900 J/cm	1.69 ft-lb/in	ASTM D256
Izod Impact, Unnotched	9.07 J/cm	17.0 ft-lb/in	ASTM D4812

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	201 Â°C @Thickness 3.20 mm	394 Â°F @Thickness 0.126 in	unannealed; ASTM D648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China