

SABIC Innovative Plastics LNP LUBRICOMP RVL36 PA 66 (Europe-Africa-Middle East)

Category : Polymer , Thermoplastic , Nylon , Nylon 66

Material Notes:

LNP* Lubricomp* RVL36 is a compound based on Nylon 66 resin containing Long Glass Fiber, PTFE.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-LUBRICOMP-RVL36-PA-66-Europe-Africa-Middle-East.php

Physical Properties	Metric	English	Comments
Density	1.50 g/cc	0.0542 lb/in ³	ISO 1183

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	185 MPa	26800 psi	5 mm/min; ISO 527
Elongation at Break	2.9 %	2.9 %	5 mm/min; ISO 527
Flexural Strength	258 MPa	37400 psi	2 mm/min; ISO 178
Flexural Modulus	8.30 GPa	1200 ksi	2 mm/min; ISO 178
Izod Impact, Notched (ISO)	20.0 kJ/m ²	9.52 ft-lb/in ²	80*10*4; ISO 180/1A

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	258 Â°C	496 Â°F	Flatw 80*10*4 sp=64mm; ISO 75/ Af

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China