

SABIC Innovative Plastics LNP Lubricomp OX95338 PPS (Asia Pacific)

Category : Polymer , Thermoplastic , Polyphenylene Sulfide (PPS)

Material Notes:

LNP* Lubricomp* OX95338 is a compound based on Polyphenylene Sulfide resin containing PTFE, Carbon Fiber. Added features of this material include: Internally Lubricated, Electrically Conductive. This data was supplied by SABIC-IP for the Asia Pacific region.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-Lubricomp-OX95338-PPS-Asia-Pacific.php

Physical Properties	Metric	English	Comments
Density	1.68 g/cc	0.0607 lb/in ³	ASTM D 792

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	84.0 MPa	12200 psi	ASTM D 638
Elongation at Break	0.70 %	0.70 %	ASTM D 638
Tensile Modulus	28.4 GPa	4120 ksi	50 mm/min; ASTM D 638
Flexural Strength	124 MPa	18000 psi	ASTM D 790
Flexural Modulus	10.82 GPa	1569 ksi	ASTM D 790
Izod Impact, Notched	0.320 J/cm @Temperature 23.0 Â°C	0.599 ft-lb/in @Temperature 73.4 Â°F	ASTM D 256
Izod Impact, Unnotched	2.67 J/cm @Temperature 23.0 Â°C	5.00 ft-lb/in @Temperature 73.4 Â°F	ASTM D 4812

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	260 Â°C @Thickness 3.20 mm	500 Â°F @Thickness 0.126 in	unannealed; ASTM D 648

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China