

SABIC Innovative Plastics LNP THERMOTUF RF008IS PA 66 (Asia Pacific)

Category : Polymer , Thermoplastic , Nylon , Nylon 66

Material Notes:

LNP* Thermotuf* RF008IS is a compound based on Nylon 66 resin containing Glass Fiber. Added features of this material include: High Impact.

Order this product through the following link:

http://www.lookpolymers.com/polymer_SABIC-Innovative-Plastics-LNP-THERMOTUF-RF008IS-PA-66-Asia-Pacific.php

Physical Properties	Metric	English	Comments
Density	1.46 g/cc	0.0527 lb/in ³	ISO 1183
Linear Mold Shrinkage, Flow	0.0020 cm/cm @Time 86400 sec	0.0020 in/in @Time 24.0 hour	ASTM D955

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	168 MPa	24400 psi	ISO 527
Elongation at Break	2.7 %	2.7 %	ISO 527
Tensile Modulus	12.5 GPa	1810 ksi	1 mm/min; ISO 527
Flexural Strength	274 MPa	39700 psi	ISO 178
Flexural Modulus	11.0 GPa	1600 ksi	ISO 178
Izod Impact, Notched (ISO)	15.0 kJ/m ²	7.14 ft-lb/in ²	80*10*4; ISO 180/1A
Izod Impact, Unnotched (ISO)	75.0 kJ/m ²	35.7 ft-lb/in ²	80*10*4; ISO 180/1U

Thermal Properties	Metric	English	Comments
Deflection Temperature at 1.8 MPa (264 psi)	247 Â°C	477 Â°F	Flatw 80*10*4 sp=64mm; ISO 75/Af

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China